



CT/AU99/00328

REC'D 19 MAY 1999

WIPO PCT

Patent Office  
Canberra

I, KIM MARSHALL, MANAGER EXAMINATION SUPPORT AND SALES,  
hereby certify that the annexed is a true copy of the Provisional specification in  
connection with Application No. PP 3326 for a patent by BAINS HARDING  
LIMITED filed on 4 May 1998.



WITNESS my hand this Thirteenth  
day of May 1999

KIM MARSHALL  
MANAGER EXAMINATION SUPPORT AND  
SALES

**PRIORITY  
DOCUMENT**

SUBMITTED OR TRANSMITTED IN  
COMPLIANCE WITH RULE 17.1(a) OR (b)

AUSTRALIA

Patents Act 1990

# **PROVISIONAL SPECIFICATION**

**INSULATION MODULE, SYSTEM AND METHOD FOR INSTALLATION  
AND MANUFACTURE**

**The invention is described in the following statement:**

## INSULATION MODULE, SYSTEM AND METHOD FOR INSTALLATION AND MANUFACTURE

This invention relates to an insulation module; a system of modules for insulating a component; a method of installation of the insulation modules; and  
5 a method of manufacture of the insulation module.

The purpose of insulation is well known, it is to reduce the impact of ambient environmental conditions on desired temperature within the insulated environment by reducing the heat transfer driving force between the insulated and ambient environments. The insulation operation involves the location and  
10 fastening of layer(s) of insulating materials, which may be of the same or different nature, about the component to be insulated. The installation may involve wrapping of an insulating material about the component but other constructions, for example panel constructions, which are adhered or otherwise secured to the component may also be employed.

15 In the industrial context, the object of insulation of a component is to maintain a desired temperature within that component. Thus in a chemical plant, tanks and pipes may hold or carry materials such as solids, gases or liquids which must be maintained within controlled temperature limits for efficient use within the process being conducted within the chemical plant.

20 Achievement of this objective is directly linked to the cost efficiency of the chemical plant as heating and cooling costs may be substantial and may be reduced by effective insulation to prevent heat loss or gain from the insulated component. Heat gain tends to be a greater problem in cool environments though in certain parts of Australia it may also be a factor requiring insulation to  
25 address.

Insulation of a chemical plant is an expensive process. Generally, it has involved the installer in the transport of the necessary cladding and insulation materials to the site where it is then manufactured into the desired form to complete the insulation job. Therefore, the process is time consuming and  
30 requires a great deal of organisation to be competently and cost effectively carried out.

Further, there are some insulation materials which, though highly suitable

for the purpose of insulation, are nevertheless considered to pose such a risk to the workers on a site that all non-insulation work must cease while the insulation is installed. This may necessitate working in night environments where the costs of lighting and incidental costs of employment are commensurately higher  
5 than during the day.

Typical of such insulation materials are fibres, particularly man-made materials such as synthetic or natural mineral fibres. One such fibre typically used in chemical plants is fibreglass. The work restraints described above are very pertinent to this fibrous material.

10 It is the object of the present invention to provide insulation modules, systems and methods for the installation of these which avoid, to the maximum practical extent, the cost and safety disadvantages of current techniques while achieving the insulation objective.

With this object in view, a first aspect of the invention provides a pre-  
15 formed insulation module comprising:

an insulation layer formed by an insulating material sealed by a sealing agent, having an inner surface contacting a component to be insulated and an outer surface; and

1 a cladding layer adhered to the insulation layer at the outer surface thereof.

20 By pre-formed is meant that the insulation module may be manufactured, as a complete insulating article, prior to transfer to, and installation at, a factory site. The factory site may be very remote to the site where the manufacturing plant is located. Such pre-fabrication of modules, which may be installed directly at the site, saves significant site costs and reduces the cost of the insulation  
25 project.

The insulating material is typically a fibrous material. Fibres may be synthetic or natural and man-made mineral fibres are especially contemplated within the scope of the present invention. Non-fibrous cellular materials such as polyurethane may be used as insulating material. The material may take any  
30 suitable rigid or flexible form, for example panels, mattresses or blankets.

The pre-formed module may be made up of any desired number of insulating layer(s) and any desired number of cladding layer(s). The insulating

layers must include at least one layer of a fibrous material, but may include further layer(s) of insulating materials of same or different nature. Insulation materials may be blended together. The construction of the pre-formed module will be dependent upon the nature of the insulation job and the cost  
5 acceptability of the module.

Preferably, the insulation module is provided with means to connect the module with another such module. Thus, in the case where the component to be insulated is a pipe or pipe fitting, such as an elbow or T-joint, a pre-formed module may cover a portion of the pipe or pipe fitting. That module is connected  
10 to another module or series of modules to complete the insulation of the pipe or pipe fitting. Conveniently, the modules in this instance may be semi-cylindrical in geometry though the module may be a fractional cylinder of any desired circumferential extent. It may be found that semi-cylindrical modules are suitable for insulation of pipes to about 20" diameter, above that diameter the  
15 modules may be made a lesser fraction of a cylinder in circumference. That is it may be found more convenient to use more than two modules to insulate a length of pipe. It will be understood that the module need not be limited in its application to the insulation of pipes and may not be circular or part circular. Many components such as tanks may be insulated using similar pre-formed  
20 modules which need not be at all cylindrical in geometry. The determining factors in selection of the design of the module are as follows: the geometry of the component to be insulated, insulation requirements and cost.

The sealing agent sealing the mineral fibres must be such as to substantially contain the fibres in normal use, that is substantially preventing  
25 environmentally unacceptable (as dictated by standards or regulations) escape or detachment of fibres, during normal use. Many sealing agents may be suitable for this application. They may be sprayed or otherwise applied to the mineral fibre product sourced from the mineral fibre supplier to achieve sealing. Poly vinyl acetate has been found to be a suitable agent which is applied to the  
30 mineral fibre product by spraying.

The module may be manufactured in any convenient manner but generally the fibrous insulating material is cut to shape, that is the shape of the

component, or part of a component to be insulated, sealed with the sealing agent and then adhered to a cladding material.

The cladding material may be a metal such as stainless steel, coated steel or aluminium; or a polymeric material. The cladding material could be a  
5 composite material. It should be resistant to environmental and plant conditions. Typically, the cladding material would require both temperature and corrosion resistance. It is adhered to the insulating layer by adhesives or other means. Possibly the sealing agent for sealing the matrix of material may be used as the adhesive agent.

10 The insulation module may be secured into position by fitting onto the component to be insulated. The fitting should take account of any thermal expansion and contraction of the insulated component. The module may also be provided on the inner surface of the insulating layer with connection means which connect it to the component, or a part of the component to be insulated.  
15 Modules can be interference or otherwise fitted together. The connection means may be mechanical or chemical in nature but must be durable taking into account environmental and plant conditions. For example, a chemical connection means such as an adhesive would require to be temperature resistant and resistant to small leakage or small plant concentrations of process  
20 materials. The connection means should allow water-tight sealing.

In a further aspect of the invention there is provided an insulation system for insulating a component comprised of pre-formed modules having an insulation layer formed by an insulating material sealed by a sealing agent and a cladding layer adhered to the insulation layer, adjacent modules being  
25 connected together by connection means to form the insulation system insulating the component.

In a still further aspect of the present invention there is provided a method of insulating a component comprising manufacturing pre-formed modules comprising an insulation layer sealed by a sealing agent ; and a cladding layer  
30 securing pre-formed modules to a component, or part of a component, and other modules to enable insulation of that component or part of the component.

Pre-formed modules making up the insulation may be connected to one

or more adjacent module(s) and/or to the component or part of the component as above described.

In a still further aspect of the present invention there is provided a method of manufacturing an insulation module comprising forming an insulation layer of  
5 insulating material; sealing the insulating material by application of a sealing agent; forming a cladding material; assembling the cladding and insulation materials; and forming the assembly into insulation modules for insulating components.

Conveniently, the sealing process is accomplished by spraying a sealing  
10 agent, for example poly vinyl acetate onto the insulating material. Other sealing agents and methods of application to the insulating material could be employed.

The insulation and cladding materials may be shaped, say into a cylindrical or other suitably shaped pre-form with controlled thickness as required for effective insulation, and adhesive may be sprayed onto the surface  
15 of the cladding material to be adhered to the sealed matrix of insulating material. The adhesive agent is then applied to the pre-form of insulating material which is then adhered to the cladding material. It is also possible for the adhesive agent to be applied only to one of the insulating or cladding layers. Other methods of application of adhesive or adhesion, that is fastening or connection,  
20 could be used in accordance with the invention.

The module, system and method of installation forming aspects of the present invention present cost and safety advantages over systems and methods currently employed for insulation. Insulation modules are also readily replaceable in the event of service failure.

25 The various aspects of the invention may be more completely understood from the following description of preferred embodiments thereof made with reference to the accompanying drawings in which:

Figure 1a is a side sectional view of a pre-formed module suitable for insulation of a length of pipe made in accordance with one embodiment of the  
30 present invention;

Figure 1b is an exploded view of two pre-formed modules showing the assembly;

Figure 2 is a perspective view of two pre-formed modules fitted together to insulate a portion of a pipe in accordance with a second embodiment of the invention;

Figure 3 is a front sectional view of a system of modules as shown in  
5 Figures 1 and 2 insulating a length of pipe;

Figure 4 is a front sectional view of a system of modules insulating a pipe fitting being an elbow; and

Figure 5 is a schematic flowchart of the manufacturing operation of an insulation module in accordance with the invention.

#### 10 Modules

Referring now to Figure 1, there is shown an insulation module 10 in accordance with one embodiment of the invention. The module 10 is of semi-cylindrical shape suitable for use in the partial insulation of a pipe, partial because the insulation module will need to co-operate with further modules to  
15 completely insulate the pipe. Modules may be designed which allow insulation by a single module of hinged or analogous construction.

The module 10 has an insulation layer 14 and a cladding layer 18. These layers are, in the case of a semi-cylindrical module, substantially semi-cylindrical and co-axial. The insulation layer 14 sits within the cladding layer 18  
20 and a neat fit is envisaged though, in the embodiment shown, an adhesive agent is employed to secure assembly of the insulation and cladding layers 14 and 18. A separate and distinct adhesive layer could be formed during manufacture. It will be seen that the cladding layer 18 is formed with greater circumferential extent than the insulation layer 14. The overlapping portions  
25 18a are connection means designed to overlap circumferentially with the cladding layer 28 of another insulation module 20 of substantially similar construction to module 10 except that the insulation and cladding layers 24 and 28 are of substantially similar circumferential extent. Other connection means of mechanical or chemical nature may be employed instead of, or additionally to,  
30 the connection means or overlapping portion 18a described.

Thus module 10 is formed with circumferential beads 16 and 17; and module 20 with circumferential beads 26 and 27. The beads may be connected



by longitudinally extending beads 126. Beads 16 and 26 are formed at ends 13 and 23 of modules 10 and 20. Beads 16, 17, 26 and 27, shown of V shape but other shapes are not excluded, strengthen the module and may act as water seals, preventing water ingress by capillary action. Beads 17 co-operate and  
 5 engage with complementary portions of beads 27 to allow at least partial locking together of the modules 10 and 20 as suggested by Figures 1b and 2. These beads may have a further function as described below. In the embodiment shown, the portion 16a of bead 16, formed on overlapping portion 18a of cladding layer 18 of module 10, is generally V shaped presenting on the inner  
 10 face 18b of overlapping portion 18a a V shaped channel which accommodates the complementary inverted V shaped bead 26 of module 20. Accommodation may involve an interference fit to achieve fastening but other connection means could be adopted. As shown in Figure 3, the connection of modules 10 and 20 may be made more secure by spot welding or riveting. Water sealing agents or  
 15 tape may also be employed for water-tight sealing.

Modules 10 and 20 are designed such that the cladding semi-cylinders are of greater length than the insulation semi-cylinders. Thus at ends 11 and 21 of the modules 10 and 20 the cladding and insulation cylinders are co-terminous. At the ends 13 and 23, the cladding semi-cylinder extends past the  
 20 end of the insulation semi-cylinder forming connection portions 19 and 29. These connection portions 19 and 29 are intended to overlap one end of adjacent insulation modules to be fastened thereto, as shown in Figure 3, in the manner typical of connection of pipes in the plumbing art. Beads 16 and 26 assist the fastening, in much the same manner as described above, with  
 25 complementary beads on adjacent modules. Bead 126 may similarly co-operate with a corresponding longitudinal bead and be made water-tight. Welding or rivetting may be employed, particularly with the circumferential beads 16, 17, 26 and 27, to complete the job by forming a substantially continuous and complete insulation layer along the length of pipe or along the  
 30 surface of a component to be insulated when the adjacent modules are correctly engaged. Fastening could also be achieved using screws or by strapping of the modules together by metal bands. The fastening is such as to achieve a water-

tight seal. Joints may be taped with water-proof tape for this purpose or sealants, such as silicone sealants, may be employed.

Referring to Figures 1 to 3, and considering the modules 10 and 20 that have been described, the overlapped end portion of each module is marked 5 110 and 120 respectively. The connection portions 19 and 29 are of substantially the same length as the end portions 110 and 120 which are terminated at one end by beads 17 and 27. Connection portions 19 and 29 are intended to be slid over the end portions 110 and 120 of adjacent modules, for example 500 and 600, until prevented from further movement by beads 17 and 10 27. Thus beads 17 and 27 act as gauges during assembly showing that adjacent modules have been correctly secured together, the final fastening being made by riveting or spot welding or otherwise using water sealing agents and tape as appropriate. At this point, the insulation layers of the adjacent modules 10, 20 and 500 come into contact, secured if desired, forming a 15 substantially continuous and complete insulation layer along the length of the pipe. Gaps are to be avoided.

Modules 10 and 20, as described above, are suitable for insulation of substantially straight lengths of pipe. The modules may be customised for insulation of pipe fittings as well as other components. Figure 4 shows a series 20 of insulation modules 30, 40, 50, 60, 70 and 80 shaped and cut to suit the radius and degree of a bend or elbow in a pipe to be insulated.

#### Method of Manufacture

The manufacture of the insulation modules 10 and 20 is shown schematically in Figure 5.

25 The material forming the insulation layer 14 may be supplied in the form of a hollow cylinder which is cut substantially along a centre line thereof to allow formation of the insulation layer 14. The linear diameter of the cylinder and thus the insulation module 10 is selected to allow an engineered clearance to a pipe to be insulated.

30 Low cost insulation materials are man-made materials made up of fibres. The fibres may be natural or synthetic, typically mineral, fibres such as fibreglass. It is such materials that have posed safety difficulties in on-site

manufacture and installation in the part. Cellular materials may also be employed, for example cellular polyurethane foams. Such materials may take the place of fibrous materials as described.

The cylindrical pre-form of the fibreglass may be sprayed with poly vinyl acetate or other suitable sealing agent to seal the insulating material. Sealing prevents escape of substantial quantities of fibres and unsatisfactory levels of such fibres in the insulation environment. Spraying could be replaced with alternative methods for applying the sealing agent, say dipping or brush application or other methods of application.

10 The application may be done before or after other manufacturing steps but typically prior to adhesion of the cladding material as prior application of the cladding layer may prevent proper sealing of the insulation material.

Typically the cladding material is metallic in nature, say of stainless steel, coated steel or aluminium. Polymeric or composite materials could also be used. In other words, the cladding material may be as conventionally employed in the insulation art and should be resistant to plant conditions, particularly corrosion and temperature resistance. The cladding material may be painted.

The cladding is likewise pre-formed into cylindrical (or other shape) lengths though having greater outer diameter than that of the cylinder of insulating material, it being remembered that overlapping portions 18a must be formed for one of the modules, module 10. Beads may be formed both circumferentially and longitudinally to assist in fastening as above described. The circumferential beads may intersect an axis of a module at any desired angle. The pre-form may then be cut to semi- or part- cylindrical or other suitable shape.

The finished modules 10 and 20 are formed by combination of adhesive and appropriate fitting techniques, for example neat or interference fitting techniques, to secure the insulation material within the cladding. Following setting or curing of the sealing agent to seal the insulation material, the adhesive may be sprayed onto one outer surface 16 of the semi-cylinder of insulation material following which it may be fitted and adhered to the semi-cylinder of cladding material to which adhesive has also been applied on an

inner surface of the cladding pre-form. Alternatively, the cladding material only may be sprayed or otherwise provided with a layer of adhesive, the insulation pre-form being pressed into position. Either the cladding or insulation materials or both could have an adhesive layer applied to them to allow adhesion. Any  
 5 adhesive must be suitable for adhesion of metallic and fibrous materials. The adhesive must be suitable for durable use in the insulated environment. A solvent based adhesive sourced from Bostik under the trade name Bostik 1831 has been found suitable.

It is not absolutely necessary for adhesives to be used, the cladding and  
 10 insulation layers 14 and 18 could be secured together by chemical bonding or mechanical techniques. Nevertheless the use of adhesives is recommended for cost efficiency and practical reasons. It is most important that the insulation and cladding layers 14 and 18 of the module 10 do not delaminate during transport to the site or before expiry of their service life.

15 The insulation module may be formed in lengths or customised to any particular component to be insulated, particularly for particular components such as pipe fittings in a process plant though other applications for the module may be envisaged. A kit of modules could be formed by cutting the lengths to smaller convenient sizes on-site or in the factory. These sub-modules are then  
 20 available for installation at the plant. It may be understood that lengths and number of modules should be convenient for cost-effective transport to site.

In the case of a bend or elbow, as described in relation to Figure 4, suitably shaped pre-forms of fibreglass and cladding material to accommodate the elbow are obtained and assembled in the same manner of manufacture as  
 25 modules 10 and 20 with cutting of the modules 30-80 to the requisite shape.

#### Method of Insulation

The installation method for a pipe or pipe fitting proceeds as follows. From design data, the pipe length is determined and insulating modules of the same kind as modules 10 and 20 described above are manufactured to allow  
 30 insulation of that pipe. For a given length of the pipe, two semi-cylindrical modules are required. A greater number of modules could be used where pipe diameter suggests that modules of lesser circumferential extent than semi-

cylindrical are more conveniently to be installed on the pipe. One module 20 is then press fitted onto the pipe. The other module 10 is likewise fitted onto the pipe with overlapping portions 18a of the cladding fitting over the surface of the first module 20 to connect them together on interference fitting of bead 16 within  
5 channel 26. Welding or riveting or other fastening is employed to complete the job. This is especially done at the circumferential beads though could also be done along the longitudinal bead. Water-tight sealing is advantageous. This may be achieved with water-proof tape and/or sealants such as silicone sealants.

10 Use of two modules is unlikely to insulate an entire pipe, other like modules are probably to be employed. In this case, adjacent modules must co-operate and be connected together to properly insulate the pipe. As has been described above, connection portions of modules 10 and 20 are overlapped with the end portions of an adjacent module and with each other suitably  
15 securing adjacent modules together to create a water seal particularly when supplemented by use of welding, rivetting and/or use of sealants and a substantially continuous and complete insulation layer along the length of pipe.

This process proceeds until the entire pipe is insulated. The invention is applicable to insulation of plant components other than pipes in which case  
20 design data is first sought for the component and pre-formed modules manufactured for the insulation job. The module(s) and systems may be utilised in concert with conventional insulation methods where design features of the plant recommend this.

Modifications and variations may be made to the present invention or  
25 consideration of the disclosure by the skilled reader of this disclosure. Such modifications and variations are considered to fall within the scope of the present invention.

DATED this 4th day of May, 1998

**BAINS HARDING LIMITED**

WATERMARK PATENT & TRADEMARK ATTORNEYS  
4TH FLOOR, "DURACK CENTRE"  
263 ADELAIDE TCE PERTH W.A. 6000 AUSTRALIA




Figure 1a







Figure 1b






Figure 5